



# e355 Mobile POS

The Verifone e355 is a compact, flexible mobile payment product designed to operate across multiple generations of smart devices for use in a variety of environments. The solution can function in standalone mode completely independent of smart devices or paired with optional frames delivering complete versatility.

- Modular design enables countless configurations with devices, frames, stands and cradles
- Interchangeable using docking connector to snap into frames for smart devices, now and in the future
- Truly universal, compatible with iOS, Android and Windows operating systems

- Includes high-speed WiFi and Bluetooth for maximum connectivity
- Large field-replaceable battery extends life of payment module beyond attached smart device
- Vibrant color display with durable Corning® Gorilla® Glass for maximum durability

# **Specifications**

#### **Processor**

400 MHz, ARM11 32-bit RISC processor

# Memory

128 MB Flash, 64 MB SDRAM

## **Display**

2.4" (320  $\times$  240) TFT LCD, Corning® Gorilla® Glass technology

# Operating System

iOS 8.0 and higher, Android 4.1 and higher, Windows 8.1 and 10

# Connectivity

WiFi (802.11 a/b/g/n), Bluetooth 4.0, micro- USB, gold-plated charging and data pins, Apple MFi-certified

#### Security

PCI PTS 4.X-approved

#### Audio

Buzzer (not adjustable)

#### **Card Readers**

Triple-track MSR, EMV-approved

#### Contactless

ISO 14443 Types A and B, ISO 18092- capable, EMVCo L1 and L2 certification, MIFARE, supports major NFC/CTLS schemes

#### Battery

DC 3.8 V/1960 mAh, rechargeable and field-replaceable

# **Environmental**

Operating temperature: -5° C to 40° C (23° F to 104° F); nonoperating environment: -20° C to 50° C (-4° F to 122° F); relative humidity: 5% to 95%, non-condensing

## **Physica**

Module only: 131 mm L  $\times$  71.5 mm W  $\times$  15.7 mm H; 193 g

#### Other Features

Optional 1D/2D barcode scanner, LED dot aiming; 1 Micro SAM reader; ISO 7816 asynchronous smart cards + EMV L1 (v4.2) support + PBOC L1; 500K insertion rating